

STAINLESS STEEL **WEATHER PROOF CANOPY** DIESEL GENERATOR

Genset Features:

8.8IYS-S

- Yanmar Water Cooled Diesel Engine
- Original over sized Stamford
- Skid mounted with no fuel tank
- Stainless weatherproof cover
- Fork lift access.
- 250 hour service intervals
- 2.1ltrs p/h @ F/L.
- · Basic Remote start controller
- 416/240 Volt Circuit Breaker.
- Eng/Alt/Controller manuals included
- Pivot input shutdown with 32vDC socket.
- 1 x 32 amp 5 pin socket
- 1 x well kill socket
- · Basic inline fuel filter
- Full with oil, coolant and load tested...

SPECIFICATIONS

Prime kVA 88 Prime kW 7.1 Prime Amps 12 Voltage 416/240 RPM 1500 Engine Brand / Model YANMAR 3TNV82 Cylinders 3 In line Fuel Tank Size No tank skid only Fuel Tank Running NA Time at 75% Load Weight

480kg (Dry)

1460 Long x 730 Wide x 110mm High

Engine Type: Water cooled, 4 stroke, Other Specifications

Dimensions in mm

Noise Level @ 7m

1500 rpm diesel engine.

Engine Fuel Consumption: 2.1 @ F/L. Eng Service Intervals: 250 Hours. Alt Brand: Stamford, +/-1.5% Voltage Regulation, Class H, AVR controlled, 4 pole, IP21.

Power Factor: 0.8 lagging.

Generator Set Controller Displays:

- Voltage Current Frequency
- Battery voltage Hour meter Fuel level

Generator Set Protection Includes:

- Low oil pressure High water temperature
- High/Low A/C voltage
 High/Low frequency
- High/Low DC battery voltage

- 1. Eng / Alt power reduction due to actual application, based on load factor, altitude & temperature is applicable, inquire for ratings.
- 2. Prime Kva Rating: 100 %, average power equal to or below 80 % of the prime rating, no time limitation.
- 3. Yanmar Engine ratings based on Ambient conditions at 1000MBAR, 27 Degrees C, 60% humidity, according to ISO3046.
- 4. Product specifications can change at any time.
- 5. Images are for illustrative purposes only & are not binding.



STAINLESS STEEL WEATHER PROOF CANOPY **DIESEL GENERATOR**

Genset Features:

10 IY-SS

- Yanmar Water Cooled Diesel Engine
- Original over sized Stamford
- Skid mounted with no fuel tank
- Stainless weatherproof cover
- Fork lift access.
- 250 hour service intervals
- 2.1ltrs p/h @ F/L.
- · Basic Remote start controller
- 416/240 Volt Circuit Breaker.
- Eng/Alt/Controller manuals included
- 1 x 32 amp 5 pin socket
- 1 x well kill socket
- · Basic inline fuel filter
- Full with oil, coolant and load tested...

SPECIFICATIONS

Prime kVA 10 Prime kW 8 Prime Amps 14 Voltage 416/240 **RPM** 1500 Engine Brand / Model YANMAR 3TNV82A Cylinders 3 In line Fuel Tank Size No tank skid only Fuel Tank Running NA Time at 75% Load

Weight

Dimensions in mm

Noise Level @ 7m

480kg (Dry)

1460 Long x 730 Wide x 110mm High

TBA

Engine Type: Water cooled, 4 stroke, Other Specifications

1500 rpm diesel engine.

Engine Fuel Consumption: 2.1 @ F/L. Eng Service Intervals: 250 Hours. Alt Brand: Stamford, +/-1.5% Voltage Regulation, Class H, AVR controlled, 4 pole, IP21.

Power Factor: 0.8 lagging.

Generator Set Controller Displays:

- Voltage
 Current
 Frequency
- Battery voltage Hour meter Fuel level

Generator Set Protection Includes:

- Low oil pressure
 High water temperature
- High/Low A/C voltage
 High/Low frequency
- High/Low DC battery voltage

- 1. Eng / Alt power reduction due to actual application, based on load factor, altitude & temperature is applicable, inquire for ratings.
- 2. Prime Kva Rating: 100 %, average power equal to or below 80 % of the prime rating, no time limitation.
- 3. Yanmar Engine ratings based on Ambient conditions at 1000MBAR, 27 Degrees C, 60% humidity, according to ISO3046.
- 4. Product specifications can change at any time. 5. Images are for illustrative purposes only & are not binding.





SPECIFICATIONS Prime kVA 12.5 Prime kW 10.4 Prime Amps 18 Voltage 416/240 **RPM** 1500 Engine Brand / Model YANMAR 3TNV88 Cylinders 3 In line Fuel Tank Size NA Fuel Tank Running NA Time at 75% Load Weight 670kg (Dry) 1450 Long x 780 Wide x 1150mm High Dimensions in mm (with bottom feet removed) Noise Level @ 7m TBA Engine Type: Water cooled, 4 stroke, Other Specifications 1500 rpm diesel engine. Engine Fuel Consumption: 3.5 @ F/L. Eng Service Intervals: 250 Hours. Alt Brand: Stamford, +/-1.5% Voltage Regulation, Class H, AVR controlled, 4

pole, IP21.

Power Factor: 0.8 lagging.

12.5 IY - SS IRRIGATION - STAINLESS STEEL WEATHER PROOF CANOPY DIESEL GENERATOR

Genset Features:

- Yanmar Water Cooled Diesel Engine
- Original oversized ALTERNATOR
- Skid mounted with no fuel tank
- Stainless weatherproof cover
- · Fork lift access.
- · 250 hour service intervals
- 2.1ltrs p/h @ F/L,
- · Basic Remote start controller
- 416/240 Volt Circuit Breaker.
- Eng/Alt/Controller manuals included
- 1 x 32 amp 5 pin socket
- 1 x well kill socket
- · Basic inline fuel filter
- Full with oil, coolant and load tested

Generator Set Controller Displays:

- Voltage Current Frequency
- Battery voltage Hour meter

Generator Set Protection Includes:

- Low oil pressure High water temperature
- High/Low A/C voltage High/Low frequency
- High/Low DC battery voltage

- 1. Eng / Alt power reduction due to actual application, based on load factor, altitude & temperature is applicable, inquire for ratings.
- 2. Prime Kva Rating: 100 %, average power equal to or below 80 % of the prime rating, no time limitation.
- 3. Yanmar Engine ratings based on Ambient conditions at 1000MBAR, 27 Degrees C, 60% humidity, according to ISO3046.
- 4. Product specifications can change at any time.
- 5. Images are for illustrative purposes only & are not binding.





SPECIFICATIONS 17

Prime kVA Prime kW 13.6 Prime Amps 21 Voltage 416/240 **RPM** 1500 Engine Brand / Model Cylinders 4 In line Fuel Tank Size NA Fuel Tank Running NA Time at 75% Load

Weight

Dimensions in mm

Noise Level @ 7m

Other Specifications

YANMAR 4TNV88

680kg (Dry)

1650 Long x 730 Wide x 1350mm High

TBA

Engine Type: Water cooled, 4 stroke,

1500 rpm diesel engine.

Engine Fuel Consumption: 4.6 @ F/L. Eng Service Intervals: 250 Hours. Alt Brand: Stamford, +/-1.5% Voltage Regulation, Class H, AVR controlled, 4

pole, IP21.

Power Factor: 0.8 lagging.

17IY - SS STAINLESS STEEL **WEATHER PROOF CANOPY** DIESEL GENERATOR

Genset Features:

- · Yanmar Water Cooled Diesel Engine
- Original over sized Stamford
- Skid mounted with fuel tank
- Stainless weatherproof cover
- Fork lift access.
- 250 hour service intervals
- 4.6 ltrs p/h @ F/L,
- · Basic Remote start controller
- 416/240 Volt Circuit Breaker.
- Eng/Alt/Controller manuals included
- Pivot input shutdown with 32vDC socket.
- 1 x 32 amp 5 pin socket
- 2 x 10 amp 3 pin socket
- · Basic fuel filter
- Full with oil, coolant and load tested...

Generator Set Controller Displays:

- Voltage Current Frequency
- Battery voltage Hour meter Fuel level

Generator Set Protection Includes:

- Low oil pressure High water temperature
- High/Low A/C voltage High/Low frequency
- High/Low DC battery voltage

- 1. Eng / Alt power reduction due to actual application, based on load factor, altitude & temperature is applicable, inquire for ratings.
- 2. Prime Kva Rating: 100 %, average power equal to or below 80 % of the prime rating, no time limitation.
- 3. Yanmar Engine ratings based on Ambient conditions at 1000MBAR, 27 Degrees C, 60% humidity, according to ISO3046.
- 4. Product specifications can change at any time.
- 5. Images are for illustrative purposes only & are not binding.